

# CanFestival3. Version 3.0

## The CANOpen stack manual

### Table of contents

1 - Introduction.....	2
1.1) The CanFestival project.....	2
1.2) What is CANopen.....	2
2 - CanFestival Features.....	3
2.1) Tools .....	3
2.2) Standard conformance.....	3
3 - How to start.....	4
3.1) Host requirements.....	4
3.2) How to get CanFestival.....	4
4 - Understanding Canfestival.....	5
4.1) CanFestival Project tree layout.....	5
4.2) Implement CanFestival in your application.....	6
4.3) CanFestival CAN interfaces.....	6
4.4) CanFestival events scheduling.....	7
5 - Linux Target.....	9
5.1) Linux Compilation and installation.....	9
5.2) Normal Linux node.....	9
5.3) Real-Time Linux node.....	9
5.4) CAN devices.....	9
6 - Windows Targets.....	11
6.1) Object Dictionary Editor GUI installation.....	11
6.2) CYGWIN.....	11
6.3) Visual Studio C++.....	12
7 - Motorola HCS12.....	13
7.1) Running a HCS12 node.....	13
8 - Example and test program:.....	14
8.1) TestMasterSlave :.....	14
8.2) gene_SYNC_HCS12 :.....	14
9 - Developing a new node.....	15
9.1) Using Dictionary Editor GUI.....	15
9.2) Generating the object Dictionary.....	21
10 - FAQ.....	23
10.1) General.....	23
10.2) LINUX.....	23
10.3) HCS12.....	23
11 - Documentation resources.....	28
12 - About the project.....	29
12.1) Contributors .....	29
12.2) Getting support.....	29
12.3) Contributing.....	30
12.4) License.....	30

# **1 - Introduction**

This document describe the CANOpen layer. CanFestival is an OpenSource (LGPL) CANOpen framework.

## **1.1) The *CanFestival* project**

This project, initiated by Edouard TISSERANT in 2001, as grown thanks to Francis DUPIN and other contributors.

Today, CanFestival focuses on providing an ANSI-C platform independent CANOpen stack that can be implemented as master or slave nodes on PCs, Real-time IPCs, and Microcontrollers.

CanFestival is a project supported by Lolitech.

## **1.2) What is *CANopen***

CANopen is a CAN based high level protocol. It defines some protocols to :

- Configure a CAN network.
- Transmit data to a specific node or in broadcast.
- Administrate the network. For example detecting a not responding node.

The documentation can be found in the Can in automation website :

<http://www.can-cia.de/canopen>

The most important document about CANopen is the normative CiA Draft Standard 301, version 4.02. You can now download with no cost the specification in Can in automation website.

To continue reading this document, let us assume that you have read some papers introducing CANopen.

## 2 - CanFestival Features

### 2.1) Tools

The CANopen library is coming with some tools :

- Object Dictionary editor GUI. WxPython Model-View-Controller based GUI, that help a lot in generating object dictionary source code for each node.
- A configure script, that let you chose compile time options such as target CPU/HOST, CAN and TIMER drivers.  
This script have not been generated with autoconf, it have been made keeping microcontroller target in mind.

### 2.2) Standard conformance

#### a) Multi-Platform

- Library source code is C-ANSI.
- Driver and examples coding conventions merely depend on target specific contributor/compiler.
- Unix compatible interfaces and examples should compile and run on any Unix system (tested on GNU/Linux and GNU/FreeBSD).

#### b) CanOpen conformance

- Should conform to DS301. V.4.02 13 february 2002.
- Master and Slave functionality implemented.
- Sending SYNC implemented.
- 1 SDO server per node. (update: more than one possible. To be more tested)
- Unlimited SDO client.
- SDO transmission mode : normal, expedited download and upload.
- Unlimited PDO receive.
- Unlimited PDO transmit.
- Object Data type implemented : 8, 16, 32 bits values, and fixed length strings.
- Slave state full implemented.
- NMT to change slave's state implemented.
- PDO transmission mode : on request, every reception of 0 to n SYNC, on event.
- NMT Heartbeat implemented : A node can be either heartbeat producer or receiver.
- NMT NodeGuard implemented : Not fully implemented.
- TIME (time Stamp) : Not implemented.
- EMCY (emergency objects) : Not implemented.

## **3 - How to start**

### **3.1) Host requirements**

What you need on your development workstation.

#### *3.1.1) Object Dictionary Editor GUI*

- Python, with
  - wxPython modules installed (at least version 2.6.3).
  - Gnosis xml tools. (Optional can also be installed locally to the project automatically will the help of a Makefile. Please see [9.1\) Using Dictionary Editor GUI](#) )

#### *3.1.2) Linux and Unix-likes*

- Linux, FreeBSD, Cygwin or any Unix environment with GNU toolchain.
- The GNU C compiler (gcc) or any other ANSI-C compiler for your target platform.
- Xpdf, and the official 301\_v04000201.pdf file in order to get GUI context sensitive help. Download the ds301 at <http://www.cancia.org/downloads/ciaspecifications/?1390>.
- GNU Make
- Bash and sed

#### *3.1.3) Windows (for native win32 target)*

- Visual Studio Express 2005 or worst.
- Microsoft platform SDK (requires Genuine Advantage)
- Cygwin (for configuration only)

### **3.2) How to get CanFestival**

Please always use CVS, this is the best way to get the most reactive support from the developer community :

```
cvs -d:pserver:anonymous@lolitech.dyndns.org:/canfestival login  
(type return, without entering a password)
```

Then, enter :

```
cvs -z3 -d:pserver:anonymous@lolitech.dyndns.org:/canfestival co -P CanFestival-3
```

## 4 - Understanding Canfestival


### 4.1) CanFestival Project tree layout

Simplified directory structure.

<b>./src</b>	ANSI-C source of CANOpen stack
<b>/include</b>	Exportables Header files
<b>./drivers</b>	Interfaces to specific platforms/HW
<b>./drivers/unix</b>	Linux and Cygwin OS interface
<b>./drivers/win32</b>	Native Win32 OS interface
<b>./drivers/timers_xeno</b>	Xenomai timers/threads (Linux only)
<b>./drivers/timers_unix</b>	Posix timers/threads (Linux, Cygwin)
<b>./drivers/can_peak_linux</b>	PeakSystem CAN library interface
<b>./drivers/can_peak_win32</b>	PeakSystem PCAN-Light interface
<b>./drivers/can_uvccm_win32</b>	Acacetus's RS232 "CAN-uVCCM" interface
<b>./drivers/can_virtual</b>	Fake CAN network (Linux, Cygwin)
<b>./drivers/hcs12</b>	HCS12 full target interface
<b>./examples</b>	<b>Examples</b>
<b>./examples/TestMasterSlave</b>	2 nodes, NMT SYNC SDO PDO, win32+unix
<b>./examples/gene_SYNC_HCS12</b>	Just send periodic SYNC on HCS12
<b>./examples/win32test</b>	Ask some DS301 infos to a node ( <b>win32</b> )
<b>./objdictgen</b>	<b>Object Dictionary editor GUI</b>
<b>./objdictgen/config</b>	Pre-defined OD profiles
<b>./objdictgen/examples</b>	Some examples/test OD
<b>./doc</b>	<b>Project and CanOpen doc</b>

## 4.2) Implement CanFestival in your application

### Implementation overview




## 4.3) CanFestival CAN interfaces


Because most CAN controllers and drivers implement FIFOs, CanFestival consider sending message as a non bloking operation.

In order to prevent reentrant calls to the stack, messages reception is implemented differently on µC and OS.:

- µC must provide interuption masking for timer and can receive IT



- OS must provide a receive thread, a timer thread and a mutex. CAN reception is a bloking operation.




#### 4.4) CanFestival events scheduling

A CanOpen node must be able to take delayed actions.

As examples, periodic sync emission, heartbeat production or SDO timeout need to set some alarms that will be called later and do the job.


μC generally do not have enough free timers to handle all the CanOpen needs directly. Moreover, CanFestival internal data may be corrupt by reentrant calls.

CanFestival implements a micro-scheduler (timer.c). It uses only one timer to mimic many timers. It manages an alarm table, and call alarms at desired time.



Scheduler can handle short clock value ranges limitation found on some µC. As an example, value range for a 16bit clock counter with 4µs tick is crossed within 0.26 seconds... Long alarms must be segmented.

Chronogram illustrate a long alarm (A) and a short periodic alarm (B), with a A value > clock range > B value. Values t0...t8 are successive setTimer call parameter values. t1 illustrates an intermediate call to TimeDispatch, caused by a delay longer than clock range. Because of long alarm segmentation, at the end of t1, TimeDispatch call will not trig any alarm callback.



## 5 - Linux Target

Linux target is default configure target.

### 5.1) Linux Compilation and installation

Call ./configure –help to see all available compile time options.

After invoking ./configure with your platform specific switches, just type make.

```
./configure [options]
make
make install
```

#### 5.1.1) Standard Linux node

Configure switch:

```
--timers=unix
```

To do a CANopen node running on PC-Linux, you need :

- A working linux distribution
- One or more Peak system PC CAN interface and the last Peak Linux driver installed.

#### 5.1.2) Real-Time Linux node

Configure switch:

```
--timers=xeno
```

To do a CANopen node running on PC-Linux, you need :

- A working Linux distribution patched with XENOMAI 2.1 or greater.
- One or more Peak system PC CAN interface and the last Peak Real Time Linux driver installed.

#### 5.1.3) CAN devices

Curently supported CAN devices and corresponding configure switch:

##### a) Peak systems

Configure switch:

```
--can=peak_linux
```

PeakSystems CAN interface is automatically chosen as default CAN interface if libpcan is present in the system.

Please download driver at <http://www.peak-system.com/linux> and follow instructions in order to install driver on your system.

##### b) Socket-Can (<http://socketcan.berlios.de>)

Configure switch:

```
--can=socket
```

##### c) LinCan

Configure switch:

```
--can=lincan
```

#### **d)Virtual CAN interfaces (for test/debug)**

Configure switch:

```
--can=virtual
```

Virtual CAN interface use Unix pipes to emulate a virtual CAN network. Each message issued from a node is repeat to all other nodes. Currently only works with nodes running in the same process, and does not support work with Xenomai.

### **5.2) Testing your CanFestival installation**

Sample provided in /example/TestMasterSlave is installed into your system during installation.

```
TestMasterSlave
```

Default can driver library is libcanfestival\_can\_virtual.so., which will simply pass CAN messages through Unix pipes between Master and Slave.

You may also want to specify different can interface and define some CAN ports. An other example using Peak's dual PCMCIA (configure and install with -can=peak) :

```
TestMasterSlave -l libcanfestival_can_peak.so -s 40 -m 41
```

## 6 - Windows Targets

CanFestival can be compiled and run on Windows platform. It is possible to use both Cygwin and win32 native runtime environment.

### 6.1) Object Dictionary Editor GUI installation.

Please refer to [8.2.1\)Using Dictionary Editor GUI](#)

### 6.2) CYGWIN

#### 6.2.1) Requirements

Cygwin have to be installed with those packages :

- gcc
- unzip
- wget
- make

Currently, the only supported CAN devices are PeakSystems ones, with PcanLight driver and library.

Please download driver at [http://www.peak-system.com/themen/download\\_gb.html](http://www.peak-system.com/themen/download_gb.html) and follow instructions in order to install driver on your system.

Install Cygwin as required, and the driver for your Peak CAN device.

Open a Cygwin terminal, and follow those instructions:

#### 6.2.2) Cygwin configuration and compilation

##### a) A single node with PcanLight and Peak CAN-USB adapter

Download the PCAN-Light Zip file for your HW ( URL from download page ):

```
wget http://www.peak-system.com/files/usb.zip
```

Extract its content into your cygwin home (it will create a "Disk" directory):

```
unzip usb.zip
```

Configure CanFestival3 providing path to the desired PcanLight implementation:

```
cd CanFestival-3
export PCAN_INCLUDE=~/Disk/PCAN-Light/Api/
export PCAN_HEADER=Pcan_usb.h
export PCAN_LIB=~/Disk/PCAN-Light/Lib/Visual\ C++/Pcan_usb.lib
./configure --can=peak_win32
make
```

In order to test, you have to use another CanFestival node, connect with a CAN cable.

```
cp ~/Disk/PCAN-Light/Pcan_usb.dll .
./examples/TestMasterSlave/TestMasterSlave \
    -l drivers/can_peak_win32/cyngcan_peak_win32.dll \
    -S 500K -M none
```

Then, on the other node :

```
./TestMasterSlave -l my_driver.so -S none -M 500K
```

Now messages are being exchanged between master and slave node.

## **b)Two nodes with PcanLight and Peak dual PCMCIA-CAN adapter**

Download the PCAN-Light Zip file for your HW ( URL from download page ):

```
wget http://www.peak-system.com/files/pccard.zip
```

Extract its content into your cygwin home (it will create a "Disk" directory):

```
unzip pccard.zip
```

The configure CanFestival3 providing path to the desired PcanLight implementation:

```
export PCAN_INCLUDE=~/Disk/PCAN-Light/Api/
export PCAN_HEADER=Pcan_pcc.h
export PCAN_LIB=~/Disk/PCAN-Light/Lib/Visual\ C++/Pcan_pcc.lib
export PCAN2_HEADER=Pcan_2pcc.
export PCAN2_LIB=~/Disk/PCAN-Light/Lib/Visual\ C++/Pcan_2pcc.lib
```

In order to test, just connect together both CAN ports of the PCMCIA card. Don't forget 120ohms terminator.

```
cp ~/Disk/PCAN-Light/Pcan_pcc.dll .
cp ~/Disk/PCAN-Light/Pcan_2pcc.dll .
./examples/TestMasterSlave/TestMasterSlave \
    -l drivers/can_peak_win32/cyngcan_peak_win32.dll
```

Messages are then exchanged between master and slave node, both inside TestMasterSlave's process.

## **6.3) Visual Studio C++**

### **6.3.1) Requirements**

Minimal Cygwin installation is required at configuration time in order to create specific header files (config.h and cancfg.h). Once this files created, cygwin is not necessary any more.

Project and solution files have been created and tested with Visual Studio Express 2005. Be sure to have installed Microsoft Platform SDK, as recommended at the end of Visual Studio installation.

### **6.3.2) Configuration with cygwin**

Follow instructions given at [4.2.2\)Cygwin configuration and compilation](#), but do neither call make nor do tests, just do configuration steps. This will create headers files accordingly to your configuration parameters, and the desired CAN hardware.

### **6.3.3) Compilation with Visual Studio**

You can either load independents "\*.vcproj" project files along your own projects in your own solution or load the provided "CanFestival-3.vc8.sln" solution files directly.

Build CanFestival-3 project first.

#### **a)PcanLight and the can\_peak\_win32 project.**

Chosen Pcan\_xxx.lib and eventually Pcan\_2xxx.lib files must be added to can\_peak\_win32 project before build of the DLL.

### **6.3.4) Testing**

Copy eventually needed dlls (ie : Pcan\_Nxxx.lib) into Release or Debug directory, and run the test program:

```
TestMasterSlave.exe -l can_peak_win32.dll
```

## 7 - Motorola HCS12

The examples have been tested on a MC9S12DG255 mounted on a Elektronikladen HCS12 T-board.

Beware that there are a few differences in the MSCAN module of the 68HC12 and HCS12 microcontroller. For a HC12, you must adapt the driver that we provide for the HCS12.

For the difference MSCAN HC12/HCS12, see the Motorola application note AN2011/D.

Configure switch:

```
--target=hcs12
```

To do a CANopen node running on a microncontroller Motorola MC9S12DP256, you need :

- The compiler GNU gcc for HC11, HC12, HCS12 : m6811-elf.  
Download the **release 3.1** at : [http://m68hc11.serveftp.org/m68hc11\\_pkg\\_rpm.php](http://m68hc11.serveftp.org/m68hc11_pkg_rpm.php)
- A board with this chip. We are using the T-board from Electronikladden.
- At least about 40 kBytes of program memory.
- A tool to flash the memory. (We are using the hight cost Lauterbach debugger).

### 7.1) Running a HCS12 node

#### 7.1.1)Compiling Canfestival:

```
./configure --target=hcs12
```

#### 7.1.2)Compiling and building an example

Enter in the folder of an HCS12 example,

```
make all
```

#### 7.1.3)Flashing the memory :

Use your prefered loader ! If you are using a debugger Lauterbach, you can load the bash file : trace32\_flash\_programmer.cmm. It loads directly the elf file.

#### 7.1.4)Connecting to a serial RS232 console :

Connect the portS(TxD0) of the HCS12 to a console configured at 19200 bauds 8N1, via a Max232 chip to adapt the electricals levels. On Linux, you can use minicom. Connecting to a console is usefull to read the messages, but not required.

#### 7.1.5)Connecting to the CAN network :

Connect the port CAN0 (pin PM0, PM1) to the network via a CAN controller. On our board, the CAN controler is a PCA82C250 chip.

#### 7.1.6)starting the node :

Press the reset of your HCS12 board.

## **8 - Example and test program:**

The “examples” directory contains some test program you can use as example for your own developments.

### **8.1) *TestMasterSlave***

```
*****
*   TestMasterSlave
*
*   A simple example for PC. It does implement 2 CanOpen
*   nodes in the same process. A master and a slave. Both
*   communicate together, exchanging periodically NMT, SYNC,
*   SDO and PDO.
*
*   Usage:
*   ./TestMasterSlave [OPTIONS]
*
*   OPTIONS:
*   -l : Can library ["libcanfestival_can_virtual.so"]
*
*   Slave:
*   -s : bus name ["0"]
*   -S : 1M,500K,250K,125K,100K,50K,20K,10K,none(disable)
*
*   Master:
*   -m : bus name ["1"]
*   -M : 1M,500K,250K,125K,100K,50K,20K,10K,none(disable)
*****
*****
```

### **8.2) *gene\_SYNC\_HCS12* :**

This is a simple CanOpen node that only send cyclic SYNC message. It demonstrate implementation on HCS12 based board.

## 9 - Developing a new node

Using provided examples as a base for your new node is generally a good idea. You can also use the provided \*.od files as a base for your node object dictionary.

Creating a new CanOpen node implies to define the Object Dictionary of this node. For that, developer have to provide a C file. This C file contains the definition of all dictionary entries, and some kind of index table that helps the stack to access some entries directly.

### 9.1) Using Dictionary Editor GUI

The Object Dictionary Editor is a WxPython based GUI that is used to create the C file needed to create a new CanOpen node.

#### 9.1.1) Installation and usage on Linux

You first have to download and install Gnosis XML modules. This is automated by a Makefile rule.

```
cd objdictgen  
make
```

Now start the editor.

```
python objdictedit.py [od files...]
```

#### 9.1.2) Installation and usage on Windows

Install Python (at least version 2.4) and wxPython (at least version 2.6.3.2).

Cygwin users can install Gnosis XML utils the same as Linux use. Just call make.

```
cd objdictgen  
make
```

Others will have to download and intall Gnosis XML by hand :

```
Gnosis Utils:  
http://freshmeat.net/projects/gnosisxml/  
http://www.gnosis.cx/download/Gnosis\_Utils.More/Gnosis\_Utils-1.2.1.win32-py24.exe  
Get latest version.
```

Download CanFestival archive and uncompress it. Use windows file explorer to go into CanFestival3\objdicgten, and double-click on objdictedit.py.

#### 9.1.3) About

The Object Dictionary editor GUI is a python application that use the Model-View-Controller design pattern. It depends on WxPython to display view on any supported platform.



CanFestival is an OpenSource (LGPL)  
CANOpen framework.

<http://canfestival.sourceforge.net>

Copyright ©: Edouard TISSERANT, Francis  
DUPIN and Laurent BESSARD

Version: CAN Festival 3.0

Contributor : LIVIC

<http://www.inrets.fr/ur/livic>

Supported by : LOLITech

<http://www.lolitech.fr>

#### 9.1.4) Main view

Top list let you choose dictionary section, bottom left list is the selected index in that dictionary, and bottom right list are edited sub-indexes.

X Objdictedit - TestMaster

File Edit Add Help

TestMaster

0x0001-0x0FFF	Data Type Definitions
0x1000-0x1029	Communication Parameters
0x1200-0x12FF	SDO Parameters
0x1400-0x15FF	Receive PDO Parameters
0x1600-0x17FF	Receive PDO Mapping

0x1000 Device Type

0x1001 Error Register

0x1005 SYNC COB ID

0x1006 Communication / Cycle Period

0x1016 Consumer Heartbeat Time


0x1018 Identity

Have Callbacks

subindex	name	type	value	access	save
0x00	Number of Entries	INTEGER8	4	Read Only	No
0x01	Vendor ID	INTEGER32	0x00000000	Read Only	No
0x02	Product Code	INTEGER32	0x00000000	Read Only	No
0x03	Revision Number	INTEGER32	0x00000000	Read Only	No
0x04	Serial Number	INTEGER32	0x00000000	Read Only	No


Add

Subindex: 0x00 Identity: Mandatory entry of struct ARRAY.




### 9.1.5)New node

Edit your node name, ID and type. Choose your inherited specific profile.




### 9.1.6)Node info

Edit your node name, ID and type.




### 9.1.7)Profile editor

Chose the used profile to edit.




Pick up optional chosen profile entries.




### 9.1.8)User types

Use User Types to implement value boundaries, and string length



### 9.1.9)Mapped variable

Add your own specific dictionary entries and associated mapped variables.



### 9.1.10) Integrated help

Using F1 key, you can get context sensitive help.

The screenshot shows the Xpdf PDF viewer window with the title "Xpdf: ../doc/301\_v04000201.pdf". The main content area displays the following text:

**Object 1018h: Identity Object**

The object at index 1018h contains general information about the device.  
The Vendor ID (sub-index 1h) contains a unique value allocated to each manufacturer.  
The manufacturer-specific Product code (sub-index 2h) identifies a specific device version.  
The manufacturer-specific Revision number (sub-index 3h) consists of a major revision number and a minor revision number. The major revision number identifies a specific CANopen behaviour. If the CANopen functionality is expanded, the major revision has to be incremented. The minor revision number identifies different versions with the same CANopen behaviour.

Below this text is a diagram illustrating the structure of the Revision number:

31	16 15	0
major revision number		minor revision number
MSB		LSB

Figure 63: Structure of Revision number

The manufacturer-specific Serial number (sub-index 4h) identifies a specific device.

OBJECT DESCRIPTION

INDEX	1018h
Name	Identity Object
Object Code	RECORD
Data Type	Identity
Category	Mandatory

The bottom of the window shows standard PDF navigation buttons (Back, Forward, Search, etc.) and a status bar indicating "Page 101 of 135" and "125%".


In order to do that, official 301\_v04000201.pdf file must be placed into doc/ directory, and xpdf must be present on your system.

**CAN Festival Reference**

A CanOpen must be able to take delayed actions.  
As examples, periodic sync emission, heartbeat production or SDO timeout need to set some alarms that will be called later and do the job.  
 $\mu$ C generally do not have many enough free timers to handle all the CanOpen needs directly. Moreover, CanFestival internal data may be corrupt by reentrant calls.  
CanFestival implement a mini-scheduler (timer.c). It uses only one timer to mimic many timers. It manage an alarm table, and call alarms at time.

Scheduler can handle short clock value ranges limitation found on some  $\mu$ C. As an example, value range counter with 4 $\mu$ s tick is crossed within 0.26 seconds... Long alarms must be segmented.

Chronogram illustrate a long alarm (A) and a short periodic alarm (B), with a A value > clock range > B




## 9.2) Generating the object Dictionary

Once object dictionary has been edited and saved, you have to generate object dictionary C code for your CanFestival node.

### 9.2.1) With GUI

Menu entry “File/Build Dictionary”.



Choose C file to create or overwrite. Header file will be also created with the same prefix as C file.

### *9.2.2)With command line*

Usage of objdictgen.py :

```
python objdictgen.py XMLFilePath CfilePath
```

## **10 - FAQ**

### **10.1) General**

#### *10.1.1) Does the code compiles on Windows ?*

Yes, with both Cygwin and Visual Studio C++.

Because CANopen layer is coded with C, put a compilation option /TC or /TP if you plan to mix C++ files. See the MSDN documentation about that.

#### *10.1.2) How to fit the library to an other microcontrôler ?*

First, be sure that you have at least 40K bytes of program memory, and about 2k of RAM.

You have to create target specific interface to HW resources. Take model on bundled interfaces provided in drivers/ and create your own interface. You also have to update Makefile.in files for target specific cflags and options. Chose -targer= configure switch to compile your specific interface.

You are welcome to contribute-back your own interfaces ! Other Canfestival users will use it and provide feedback, tests and enhancements.

#### *10.1.3) Is CanFestival3 conform to DS301 v.4.02 ?*

Thanks to Philippe Fourey (IUT of Valence), a slave node have been tested with the National Instrument CanOpen Conformance Test. It passed the test with success.

Some very small unconformity have been found in very unusual situations, for example in the SDO code response to wrong messages.

### **10.2) LINUX**

#### *10.2.1) How to use a Peaksystem CAN board ?*

Just install peak driver and then compile and install Canfestival. Peak driver is detected at compile time.

#### *10.2.2) How to use an unsupported CAN board ?*

You have to install the specific driver on your system, with necessary libs and headers.

Use can\_peak.c/h or can\_virtual.c/h as an example, and adapt it to your driver API.

Execute configure script and choose --can=mydriver

### **10.3) Win32**

Compatibility:

- Code was compiled MS VisualStudio 2003.NET and VisualStudio 2005.NET for WindowsXP with ANSI and UNICODE configurations and for WindowsCE 5.0.
- Some preliminary testing was done, but not enough to be used in mission critical projects.

Additional Features:

- Non-integral integers support implementation UNS24, UNS40, UNS48 etc.

- When enable debug output with DEBUG\_WAR\_CONSOLE\_ON or DEBUG\_ERR\_CONSOLE\_ON, you can navigate in CanFestival source code by double clicking at diagnostic lines in VisualStudio.NET 200X Debug Output Window.

Custom size integral types such as INTEGER24, UNS40, INTEGER56 etc. have been defined as 64 bits integers. You will need to replace sizeof(TYPE) operators to sizeof\_TYPE definitions in generated code, i.e. replace sizeof(UNS40) with sizeof\_UNSA40.

## **10.4) HCS12**

### *10.4.1) Which board are you using ?*

A T-board from elektronikladen with a MC9S12DP256 or MC9S12DG256.

### *10.4.2) Does the code compile with an other compiler than GNU gcc ?*

It is known to work with Metrowerks CodeWarrior. Here are some tips from Philippe Foureyeys. :

#### **a) Interrupt functions**

##### **i) Code for GCC:**

```
// prototype
void __attribute__((interrupt)) timer3Hdl(void):
// function
void __attribute__((interrupt)) timer3Hdl(void) {...}
```

##### **ii) Code for CodeWarrior**

```
// protoype
void interrupt timer3Hdl(void);
// function
pragma CODE_SEG__NEAR_SEG_NON_BANKED
void interrupt timer3Hdl(void)
{...}
pragma CODE_SEG_DEFAULT
```

#### **b) Interrupt lock, unlock**

##### **i) Code for GCC**

```
void unlock (void)
{
    __asm__ __volatile__("cli");
}
void lock (void)
{
    unsigned short mask;
    __asm__ __volatile__("tpa\n\tsei": "=d" (mask));
}
```

## **ii)Code for CodeWarrior**

```
void unlock (void)
{
    __asm("cli");
}

void lock (void)
{
    unsigned short mask;
    __asm
    {
        tpa:tsei:"=d" (mask);
    }
}
```

## **c)Initialize function**

### **i)Code for GCC**

```
void initCanHCS12 (void)
{
    //Init the HCS12 microcontroller for CanOpen
    initHCS12();
    // Init the HCS12 CAN driver
    const canBusInit bi0 = {
        0,      /* no low power */          */
        0,      /* no time stamp */         */
        1,      /* enable MSCAN */          */
        0,      /* clock source : oscillator (In fact, it is not used) */
        0,      /* no loop back */           */
        0,      /* no listen only */          */
        0,      /* no low pass filter for wk up */
        CAN_Baudrates[CAN_BAUDRATE_250K],
    {
        0x00,    /* Filter on 16 bits.
                    See Motorola Block Guide V02.14 fig 4-3 */
        0x00, 0xFF, /* filter 0 hight accept all msg */
        0x00, 0xFF, /* filter 0 low accept all msg */
        0x00, 0xFF, /* filter 1 hight filter all of msg */
        0x00, 0xFF, /* filter 1 low filter all of msg */
        0x00, 0xFF, /* filter 2 hight filter most of msg */
        0x00, 0xFF, /* filter 2 low filter most of msg */
        0x00, 0xFF, /* filter 3 hight filter most of msg */
        0x00, 0xFF, /* filter 3 low filter most of msg */
    }
};
```

## ii)Code for CodeWarrior

```

void initCanHCS12 (void)
{
    //Init the HCS12 microcontroller for CanOpen
    initHCS12();
    // Init the HCS12 CAN driver
    const canBusInit bio = {
        0, /* no low power */ 
        0, /* no time stamp */ 
        1, /* enable MSCAN */ 
        0, /* clock source : oscillator (In fact, it is not used) */ 
        0, /* no loop back */ 
        0, /* no listen only */ 
        0, /* no low pass filter for wk up */ 
    {
        1, /* clksrc */ 
        3, /* brp */ 
        0, /* sjw */ 
        0, /* samp */ 
        1, /* tseg2 */ 
        12,/* tseg1 */ 
    },
    {
        0x00, /* Filter on 16 bits.
                See Motorola Block Guide V02.14 fig 4-3 */
        0x00, 0xFF, /* filter 0 hight accept all msg */ 
        0x00, 0xFF, /* filter 0 low accept all msg */ 
        0x00, 0xFF, /* filter 1 hight filter all of msg */ 
        0x00, 0xFF, /* filter 1 low filter all of msg */ 
        0x00, 0xFF, /* filter 2 hight filter most of msg */ 
        0x00, 0xFF, /* filter 2 low filter most of msg */ 
        0x00, 0xFF, /* filter 3 hight filter most of msg */ 
        0x00, 0xFF, /* filter 3 low filter most of msg */ 
    }
};


```

### 10.4.3)Who to use warnings and errors messages ?

#### a)Warnings messages

<b>DEBUG_WAR_CONSOLE_ON</b>	<b>DEBUG_CAN</b>	<b>PrintMsg-WarTo-Console</b>	<b>Printing long message on console</b>	<b>Printing message on console.</b> (number value only)	<b>short on</b>	<b>Sending number and value in a PDO.</b> , only if the node is a slave, in operational state.
DEF	DEF	1		yes		
DEF	DEF	0	yes			
DEF	UNDEF	1				
DEF	UNDEF	0				
UNDEF	X	X				

## b)Errors messages

<b>DEBUG_E RR_CONS OLE_ON</b>	<b>DEBUG _CAN</b>	<b>PDO _ERROR</b>	<b>PrintMsg- ErrTo- Console</b>	<b>Printing long message on console</b>	<b>Printing short message on console. (number and value only)</b>	<b>Sending number and value in a PDO., only if the node is a slave, in operational state.</b>
DEF	DEF	X	1		yes	yes
DEF	DEF	X	0	yes		yes
DEF	UNDEF	X	1			yes
DEF	UNDEF	X	0			yes
UNDEF	X	DEF	X			yes
UNDEF	X	UNDEF	X			

### 10.4.4)Does the code works in banked memory ?

No. Today it seems that the port of gcc is bogged for using the banked memory. So, unfortunately, we are limited to 48 Kbytes of memory code.

### 10.4.5)What GCC version are you using ?

We are using the stable RPM release 2.2 :

- GNU Gcc 3.0.4. Build 20030501
- Newlib 1.10.0 Build 20030421
- GNU Binutils 2.12.1 Build 20030427

# **11 - Documentation resources**

## **a)CIA : Can in Automation**

Many documentation on CANopen.

<http://www.can-cia.de>

## **b)Resources and training in CANopen**

<http://www.esacademy.com>

## **c)Elektronikladen HCS12 T-board**

[http://www.elektronikladen.de/en\\_hcs12tb.html](http://www.elektronikladen.de/en_hcs12tb.html)

## **d)Gnu gcc compiler for HC12**

[http://m68hc11.serveftp.org/m68hc11\\_port.php](http://m68hc11.serveftp.org/m68hc11_port.php)

## **e)Motorola documentation on HC12**

[http://www.freescale.com/webapp/sps/site/prod\\_summary.jsp?code=MC9S12DP256](http://www.freescale.com/webapp/sps/site/prod_summary.jsp?code=MC9S12DP256)

## **f)Lauterbach debugger for HC12**

<http://www.lauterbach.com>

## **g)Python language**

<http://www.python.org>

## **12 - About the project**

### **12.1) Contributors**



Unité mixte de recherche INRETS-LCPC  
sur les Interractions Véhicule-Infrastructure-Conducteur  
14, route de la minière  
78000 Versailles  
FRANCE

Tel : +33 1 40 43 29 01

<http://www.inrets.fr/ur/livic>

**Contributors :** Francis DUPIN  
Camille BOSSARD  
Laurent ROMIEUX



LOLITECH  
204, rue du Haut du Pin  
88470 Saint-Michel sur Meurthe  
FRANCE

Tel : +33 3 29 52 95 67

<http://www.lolitech.fr>

**Contributors :** Edouard TISSERANT (Original author)  
Laurent BESSARD

Many thanks to the other contributors for their great work:

Raphael ZULLIGER  
David DUMINY (sté A6R)  
Zakaria BELAMRI

### **12.2) Getting support**

Send your feedback and bug reports to [canfestival-devel@lists.sourceforge.net](mailto:canfestival-devel@lists.sourceforge.net).

For commercial support, training and specific integration and developments, please ask LOLITECH (see contributors).

## **12.3) Contributing**

You are free to contribute your specific interfaces back to the project. This way, you can hope to get support from CanFestival users community.

Please send your patch to [canfestival-devel@lists.sourceforge.net](mailto:canfestival-devel@lists.sourceforge.net).

Feel free to create some new predefined DS-4xx profiles (\*.prf) in objdictgen/config, as much as possible respectful to the official specifications.

## **12.4) License**

All the project is licensed with LGPL. This mean you can link CanFestival with any code without being obliged to publish it.

```
#This file is part of CanFestival, a library implementing CanOpen Stack.  
#  
#Copyright (C): Edouard TISSERANT, Francis DUPIN and Laurent BESSARD  
#  
#See COPYING file for copyrights details.  
#  
#This library is free software; you can redistribute it and/or  
#modify it under the terms of the GNU Lesser General Public  
#License as published by the Free Software Foundation; either  
#version 2.1 of the License, or (at your option) any later version.  
#  
#This library is distributed in the hope that it will be useful,  
#but WITHOUT ANY WARRANTY; without even the implied warranty of  
#MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU  
#Lesser General Public License for more details.  
#  
#You should have received a copy of the GNU Lesser General Public  
#License along with this library; if not, write to the Free Software  
#Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA
```